



Carxol SUPREME ULTRA 10W/40 API SN-SUPER SYNTHETIC

DESCRIPTION

Supreme Ultra 10W/40 API SN Super Synthetic is premium multi grades oil. This product is launched to meet the requirements of both gasoline and diesel engine (Passenger Cars and Light Industrial Vehicles). This could be used in all operating conditions. This product is made with both high performance base oil and additives. It furnishes the engine with high warm startness and oxidation obstruction. It opposes consumption, rust and wear, giving the vehicle long life.

Performance Features

- Synthetic technology Engine oil, Helps to protect against sludge and wear.
- API SN meets the latest API Level.
- Offering advance Performance.
- Giving excellent mileage comparatively other market lubricants / brands.
- It has good cold-start flow properties and provides adequate protection at higher operating temperature.

TYPICAL PHYSICAL CHARACTERISTICS

TEST	RESULTS
Density @ 15 °C	0.8685
Viscosity @ 100 °C	14.50
Viscosity @ 40 °C	99.8
Viscosity Index	150
Flash Point (CoC)	230
Pour Point °C	-33

APPLICATIONS

- Supreme Ultra 10W/40 super synthetic API SN is recommended for gasoline fueled automobiles and light duty Vans.
- High performance cars equipped with T-GDI , GDI , EFI , and VVT
- Sports Vehicles.

NTN: 1360213 - 6

HEAD OFFICE:

11-Dockyard Road, West Wharf Industrial Area,
 P. O. Box No. 4992, Karachi-74000, Pakistan.
 Tel.: +92-21-32314066 - 8 Fax: +92-21-32310421


REGIONAL OFFICE:

F-102, Regency Plaza, 120-P, Mini Market,
 Gulberg-II, Lahore. Tel.: +92-42-35756728, 35757759
 Fax: +92-42-35713250

E-mail: hol@haroonoils.com
www.haroonoils.com
E-mail: hollahore@haroonoils.com