



DEXOL 200 MONO

DESCRIPTION

Dexol 200 Mono engine oil (API class level CD / SF is best for use in automotive gasoline diesel engines. It is also suitable for naturally aspirated diesel engines in moderate duty service and provides best Performance in the application for which they are intended. Its keeps the engine clean, protects against mechanical wear and also protect against low temperature rust and corrosion.

PERFORMANCE FEATURES

- Provide excellent Performance.
- Keep the Engine clean
- Protect against mechanical wear.
- Protect against low temperature, rusting wear and corrosion
- Confirms API class level CD / SF.

TYPICAL CHARACTERISTICS

TESTS	SAE-50
Density at 15 C	0.901
Viscosity at 100 C. cSt	18.3
Viscosity Index Min.	90
Flash Point C(CoC)	200
Pour Point C	-6

APPLICATIONS

- Can be used in the oldest four cycled diesel engines Trucks, Pickups, Buses, Vans as well as in CNG kits fitted cars.

NTN: 1360213 - 6

HEAD OFFICE:

11-Dockyard Road, West Wharf Industrial Area,
P. O. Box No. 4992, Karachi-74000, Pakistan.
Tel.: +92-21-32314066 - 8 Fax: +92-21-32310421



REGIONAL OFFICE:

F-102, Regency Plaza, 120-P, Mini Market,
Gulberg-II, Lahore. Tel.: +92-42-35756728, 35757759
Fax: +92-42-35713250