



## DEXOL 250 MULTI

### DESCRIPTION

This grade is a blend of high quality solvent extracted base oil and contains selected additives.

It meets the API Performance level classification CD / SF SAE 20W/50. Provides more lubrications and useful in all weather conditions it also provides excellent protection from rust and corrosion. TBN quantity neutralize acidic effects.

### PERFORMANCE FEATURES

- It is multi-grade oil useful in all weathers.
- Provides extra lubricity
- Having detergent and dispersant properties
- Confirms US Military Performance level MIL-L-2104 B.

### TYPICAL CHARACTERISTICS

TESTS	SAE 20 W/ 50
Density at 15 C	0.900
Viscosity at 100 C, cst	19.0
Viscosity Index Min	120
Flash Point C CoC)	245
Pour Point C	--15

### APPLICATIONS

- It is multi-grade oil especially suitable for Japanese model trucks, busses, wagons and Bedford vehicles, tractors and fishing trawlers.

NTN: 1360213 - 6

#### HEAD OFFICE:

11-Dockyard Road, West Wharf Industrial Area,  
P. O. Box No. 4992, Karachi-74000, Pakistan.  
Tel.: +92-21-32314066 - 8 Fax: +92-21-32310421



#### REGIONAL OFFICE:

F-102, Regency Plaza, 120-P, Mini Market,  
Gulberg-II, Lahore. Tel.: +92-42-35756728, 35757759  
Fax: +92-42-35713250

E-mail: [hol@haroonoils.com](mailto:hol@haroonoils.com)[www.haroonoils.com](http://www.haroonoils.com)E-mail: [hollaore@haroonoils.com](mailto:hollaore@haroonoils.com)