



DEXOL 300 MONO

DESCRIPTION

Dexol 300 MONO SAE 50 API CF/SF is a high performance mono grade heavy duty diesel engine oil. It is formulated from advance technology base oils and additives, It provides the engine high thermal stability and oxidation resistance.

Performance Features

- Dexol 300 MONO SAE 50 API Level CF/SF .
- It is high performance mono grade heavy duty diesel engine oil .
- It is specially engineered for performance in intercool. Turbo charged engine operating under severe on and off highway conditions.
- It meets all current industry standard requirement of major engine makers recommending API Level CF/SF.
- It provide maximum cleanliness.
- It reduced engine maintenance cost.
- It has superior thermo oxidative stability.
- It also has excellent anti wear technology.

TYPICAL PHYSICAL CHARACTERISTICS

TEST	RESULTS
Density @ 15 °C	0.900
Viscosity @ 100 °C	19.00
Viscosity @ 40 °C	203.3
Viscosity Index	105
Flash Point (COC)	250
Pour Point °C	-18

APPLICATIONS

- It is a heavy duty engine oil recommended for turbo charged and non turbo charged engines .
- Mixed fleet of diesel engine (High Speed , Four Stroke , Turbo Charged and naturally aspirated) .
- Commercial Road Transport like buses truck and trailers.
- It can be used in older trucks and buses as well. PP
- High speed diesel engines in marine service (fishing boats, river transport.
- Agricultural tractors.

NTN: 1360213 - 6

HEAD OFFICE:

11-Dockyard Road, West Wharf Industrial Area,
P. O. Box No. 4992, Karachi-74000, Pakistan.
Tel.: +92-21-32314066 - 8 Fax: +92-21-32310421



REGIONAL OFFICE:

F-102, Regency Plaza, 120-P, Mini Market,
Gulberg-II, Lahore. Tel.: +92-42-35756728, 35757759
Fax: +92-42-35713250

E-mail: hol@haroonoils.com

www.haroonoils.com

E-mail: hollaore@haroonoils.com