



DEXOL 350 Multi

DESCRIPTION

Dexol 350 Multi Oil is blended from high quality solvent extracted base oil and contains selective additives. It is formulated API classification level CF/SF, SAE-20W/50. It carries away heat, prevents from rust/corrosion and keeps away dirt and enhance engine life. It is suitable all seasons.

PERFORMANCE FEATURES

- It is multigrade oil and protects engine from all weather effects.
- Confirms US Military Performance level MIL-L-2104 C.

TYPICAL CHARACTERISTICS

TESTS	SAW 20/50
Density at 15 °C	0.900
Viscosity @ 100 °C, Cst	19.0
Viscosity Index	120
Flash Point °C (CoC)	248
Pour Point °C	-15

APPLICATIONS

- Dexol 350 Multi oil is specially blended for 4 stroke diesel engines, it is equally suitable for civic area and highway vehicles. Also suitable for tractors, generators and fishing trawlers.
- It is suitable for turbo charged and super charged heavy-duty diesel engines especially for NISSAN, ISUZU, TOYOTA, MAZDA, and KIA vehicles.
- Dexol 350 Multi is best design for heavy-duty loaders.

NTN: 1360213 - 6

HEAD OFFICE:

11-Dockyard Road, West Wharf Industrial Area,
P. O. Box No. 4992, Karachi-74000, Pakistan.
Tel.: +92-21-32314066 - 8 Fax: +92-21-32310421



REGIONAL OFFICE:

F-102, Regency Plaza, 120-P, Mini Market,
Gulberg-II, Lahore. Tel.: +92-42-35756728, 35757759
Fax: +92-42-35713250

E-mail: hol@haroonoils.comwww.haroonoils.comE-mail: hollaore@haroonoils.com