



DEXOL 400 Multi SAE 20W/50 API CF-4/SG

Description

Dexol 400 Multi is high performance multi grade engine oil, especially designed for lubrication a wide range of diesel and gasoline engines requiring API CF-4/SG performance lubricants. Highly effected detergent additive system, provides excellent protection against piston deposits, wear, rust and corrosion. It gives long engine life, maintain engine power and efficiency and lower service cost.

Performance Features

- It meets the API Level CF-4/SG
- This oil is designated to provide improved control over high temperature piston deposits, wear and soot accumulation in the oil, enhance performance and controlling oil oxidation.
- Due to the use of shear stable viscosity index improver, the viscosity stays in its grade, so that the oil continues to provide a strong lubricating film between the parts of the engine.

TYPICAL PHYSICAL CHARACTERISTICS

TEST	RESULTS
Density @ 15 °C	0.8849
Viscosity @ 100 °C	19.20
Viscosity @ 40 °C	174.9
Viscosity Index	125
Flash Point (COC)	240
Pour Point °C	-24

APPLICATIONS

- Dexol 400 Multi SAE 20W/50 API CF-4/SG is designed for mixed fleet of diesel engines (Four stroke , High speed , Turbo Charged etc).
- Mixed fleet gasoline engines.
- Commercial road transport
- Off highway vehicles and plants.
- Small diesel engine in marine services.

NTN: 1360213 - 6

HEAD OFFICE:

11-Dockyard Road, West Wharf Industrial Area,
P. O. Box No. 4992, Karachi-74000, Pakistan.
Tel.: +92-21-32314066 - 8 Fax: +92-21-32310421



REGIONAL OFFICE:

F-102, Regency Plaza, 120-P, Mini Market,
Gulberg-II, Lahore. Tel.: +92-42-35756728, 35757759
Fax: +92-42-35713250

E-mail: hol@haroonoils.com

www.haroonoils.com

E-mail: hollaore@haroonoils.com