



1964 - 2014



HAROON OILS LIMITED

The *Lifeblood* of All Engines!

DEXOL 550 Multi

DESCRIPTION

Dexol 550 Multi Engine Oil is manufactured from high quality paraffinic base oils. It is highly refined multi-grade Engine oil formulated with special type of additives package. The performance of this oil in diesel & petrol engines is very high caliber and has a superior nature.

PERFORMANCE FEATURES

- Dexol 550 Multi Engine Oil (API-CH-4 / SJ SAE 15W/40) is best for use in high speed four stroke engines operating on diesel fuels with sulphur levels not exceeding 0.5% off highway or 0.5% on highway.
- It meets the level of API specification CH-4 / SJ SAE 15W/40.
- It controls high temperature deposit plus reduces wear, Corrosion, foaming, oxidations, and soot accumulation.
- It also meets VW500.00/501.01/505.00 & MB 228.1.
- Blended from HVI base stocks.
- When using diesel fuels with typical sulphur levels above 0.5% Weight oil drain intervals must be reduced.

TYPICAL PHYSICAL CHARACTERISTICS

	ASTM NOS.	15W/40
KINEMATIC VISCOSITY @ 100 °C	D-445	14.8
VISCOSITY INDEX	0-2270	135
DENSITY @ 15 °C Kg/1	D-1298	0.893
FLASH POINT °C (CoC)	D-92	205
POUR POINT °C	D-97	-21
SULPHATED ASH		125%
TOTAL BASE NUMBER		10

APPLICATIONS

- High-speed four stroke diesel engines run on low sulphur fuel and designed to meet exhaust emission standard.
- It is also useful for petrol, diesel vehicles and construction machinery.

NTN: 1360213 - 6

HEAD OFFICE:

11-Dockyard Road, West Wharf Industrial Area,
P. O. Box No. 4992, Karachi-74000, Pakistan.
Tel.: +92-21-32314066 - 8 Fax: +92-21-32310421



REGIONAL OFFICE:

F-102, Regency Plaza, 120-P, Mini Market,
Gulberg-II, Lahore. Tel.: +92-42-35756728, 35757759
Fax: +92-42-35713250

E-mail: hol@haroonoils.com

www.haroonoils.com

E-mail: hollaore@haroonoils.com