



## **DEXOL 600 Multi SAE 15W/40 API CI-4**

### DESCRIPTION

DEXOL 600 Multi SAE 15W/40 API CI-4 is a high performance heavy-duty diesel engine oil for trucks, buses, stationary engines, construction equipment, farming machinery, mining equipments, boats and other on-road & off-road applications. It provides superior protection of engine parts under heavy loads. Prevents leaks on high mileage engines. This oil exhibit excellent detergency and antiwear properties as well as good oxidation and soot control.

### Performance Features

- This product meets API CI-4 specifications
- Increases fuel economy due to ultra-low vaporization loss.
- Excellent control on engine deposit even at high temperature ensures maximum engine power.
- High oxidation stability to protect against sludge thickening that maintains oil viscosity and enhances oil drain interval.
- Special ash-less dispersant ensures high quality cleanliness of engine parts and enhance engine life.
- Advanced anti-wear additive system provides consistent lubrication and protects engine from wear.

### TYPICAL PHYSICAL CHARACTERISTICS

TEST	RESULTS
Density @ 15 °C	0.8685
Viscosity @ 100 °C	14.5
Viscosity @ 40 °C	105.2
Viscosity Index	140
Flash Point (COC)	234
Pour Point °C	-27

### APPLICATIONS

- Meets the latest engine oil specifications for major diesel engine manufacturers.
- This oil is recommended for four-stroke, high-speed and naturally aspirated engines.
- High performance multi-grade oil specially formulated for turbocharged heavy duty diesel engines.
- High-speed stationary power generation units.
- Heavy earth-moving equipments used in the construction industry and Inter-city fleet operation.

NTN: 1360213 - 6

#### HEAD OFFICE:

11-Dockyard Road, West Wharf Industrial Area,  
P. O. Box No. 4992, Karachi-74000, Pakistan.  
Tel.: +92-21-32314066 - 8 Fax: +92-21-32310421



#### REGIONAL OFFICE:

F-102, Regency Plaza, 120-P, Mini Market,  
Gulberg-II, Lahore. Tel.: +92-42-35756728, 35757759  
Fax: +92-42-35713250

E-mail: [hol@haroonoils.com](mailto:hol@haroonoils.com)[www.haroonoils.com](http://www.haroonoils.com)E-mail: [hollahore@haroonoils.com](mailto:hollahore@haroonoils.com)