



HAROON MP GREASE

DESCRIPTION

Haroon MP Grease for all type of automotive application. Grease of highest quality of NLGI-2 consistency. It provides superior lubrication for the components of automotive.

TYPICAL CHARACTERISTICS

TEST	HAROON MP GREASE
BASE	LITHIUM SOAP
DROP POINT MIN	180
PETRATION 25C	265-295
NLGI NUMBER	2

NTN: 1360213 - 6

HEAD OFFICE:

11-Dockyard Road, West Wharf Industrial Area,
 P. O. Box No. 4992, Karachi-74000, Pakistan.
 Tel.: +92-21-32314066 - 8 Fax: +92-21-32310421


REGIONAL OFFICE:

F-102, Regency Plaza, 120-P, Mini Market,
 Gulberg-II, Lahore. Tel.: +92-42-35756728, 35757759
 Fax: +92-42-35713250



Textile General Machinery Oil				
	68	100	150	220
Density @ 15.6 °C	0.906	0.913	0.924	0.926
Viscosity@40 °C cSt	68	108	151	217
Viscosity@100 °C cSt	8.02	10.44	13.12	16.7
Viscosity Index	80	72	75	77
Flash Point °C (Coc) Min	226	236	240	250
Pour Point Point °C Max	-6	-3	-3	-3

NTN: 1360213 - 6

HEAD OFFICE:

11-Dockyard Road, West Wharf Industrial Area,
P. O. Box No. 4992, Karachi-74000, Pakistan.
Tel.: +92-21-32314066 - 8 Fax: +92-21-32310421

**REGIONAL OFFICE:**

F-102, Regency Plaza, 120-P, Mini Market,
Gulberg-II, Lahore. Tel.: +92-42-35756728, 35757759
Fax: +92-42-35713250

E-mail: hol@haroonoils.comwww.haroonoils.comE-mail: hollahore@haroonoils.com



CNG Compressor Oil				
	46	68	100	150
Density @ 15.6 °C	0.883	0.889	0.894	0.899
Viscosity@40 °C cSt	44.61	66.7	104.6	147.1
Viscosity@100 °C cSt	6.74	8.62	11.6	14.7
Viscosity Index	104	100	98	99
Flash Point °C (Coc) Min	226	236	240	250
Pour Point Point °C Max	-6	-3	-3	-3

NTN: 1360213 - 6

HEAD OFFICE:

11-Dockyard Road, West Wharf Industrial Area,
P. O. Box No. 4992, Karachi-74000, Pakistan.
Tel.: +92-21-32314066 - 8 Fax: +92-21-32310421

**REGIONAL OFFICE:**

F-102, Regency Plaza, 120-P, Mini Market,
Gulberg-II, Lahore. Tel.: +92-42-35756728, 35757759
Fax: +92-42-35713250

E-mail: hol@haroonoils.comwww.haroonoils.comE-mail: hollahore@haroonoils.com



Turbine Oils				
	32	46	68	100
Density @ 15.6°C	0.876	0.882	0.888	0.893
Viscosity@40°C cSt	32	46	68	100
Viscosity@ 100°C cSt	5.37	6.72	8.62	11.2
Viscosity Index	100	98	97	97
Flash Point °c (Coc) Min	205	218	220	220
Pour Point Point °c Max	-6	-6	-6	-6

NTN: 1360213 - 6

HEAD OFFICE:

11-Dockyard Road, West Wharf Industrial Area,
P. O. Box No. 4992, Karachi-74000, Pakistan.
Tel.: +92-21-32314066 - 8 Fax: +92-21-32310421

**REGIONAL OFFICE:**

F-102, Regency Plaza, 120-P, Mini Market,
Gulberg-II, Lahore. Tel.: +92-42-35756728, 35757759
Fax: +92-42-35713250

E-mail: hol@haroonoils.comwww.haroonoils.comE-mail: hollahore@haroonoils.com



Power Marine Engine Oil 40	
Density @ 15.6 °C	0.900 - 0.950
Viscosity@100°C cSt	12.5 - 16.0
Viscosity Index	95
Flash Point °c (Coc) Min	200
Pour Point Point °c Max	-18
TBN	40

NTN: 1360213 - 6

HEAD OFFICE:

11-Dockyard Road, West Wharf Industrial Area,
P. O. Box No. 4992, Karachi-74000, Pakistan.
Tel.: +92-21-32314066 - 8 Fax: +92-21-32310421

**REGIONAL OFFICE:**

F-102, Regency Plaza, 120-P, Mini Market,
Gulberg-II, Lahore. Tel.: +92-42-35756728, 35757759
Fax: +92-42-35713250

E-mail: hol@haroonoils.comwww.haroonoils.comE-mail: hollahore@haroonoils.com



Steam Cylinder Oil	
Density @ 15.6° C	0.930 - 0.950
Viscosity@40°C cSt	795.2
Viscosity@100°C cSt	35.54
Viscosity Index	70
Flash Point °c (Coc) Min	280
Pour Point Point °c Max	-3

NTN: 1360213 - 6

HEAD OFFICE:

11-Dockyard Road, West Wharf Industrial Area,
P. O. Box No. 4992, Karachi-74000, Pakistan.
Tel.: +92-21-32314066 - 8 Fax: +92-21-32310421

**REGIONAL OFFICE:**

F-102, Regency Plaza, 120-P, Mini Market,
Gulberg-II, Lahore. Tel.: +92-42-35756728, 35757759
Fax: +92-42-35713250