



HAROON OILS LIMITED

The Lifeblood of All Engines!

1964 - 2014

Mighty4T SAE-20W/50 API SG/CD

DESCRIPTION

MIGHTY 4T SAE 20W/50 API Level SG/CD is a high performance advance technology motorcycle engine oil that meets technical standards for Local manufacturers, Japanese and European motorcycles equipped with catalytic converter. Tri-facet low-friction modern technology protects engine, clutch and gearboxes components to provide optimum performance and extended oil service life. R&D work was done to ensure the upgraded formulation provided enhanced gear and wear protection in motorcycle transmissions.

Performance Features

- JASO 4T MA2 API SG/CD
- Tri-facet additive technology provides outstanding resistance against clutch slippage, ensures protection against engine wear and pitting in gear-box.
- Easy starting at low temperature and maintains adequate oil film at high temperatures to protect engine components from wear.
- Low friction MA2 additive technology ideally compatible with wet-clutch and facilitates smooth gear shifts.
- Increased engine life and engine power retention.
- Provides a protective film on engine parts in all conditions.
- Superior cleanliness for engine and piston rings ensures longer engine service life.

TYPICAL PHYSICAL CHARACTERISTICS

TEST	RESULTS
Density @ 15 °C	0.8763
Viscosity @ 100 °C	18.24
Viscosity @ 40 °C	163.5
Viscosity Index	124
Flash Point (COC)	234
Pour Point °C	-24

APPLICATION

- Highly recommended for Local manufactured, Japanese and European motorcycles.
- Recommended for 4-stroke Motorcycle.
- MIGHTY 4T SAE 20W/50 API SG/CD prime recommendation for competition and applications. • It is also well suited to a wide range of four-stroke petrol engines used in generators, lawnmowers, and light power equipments.

NTN: 1360213 - 6

HEAD OFFICE:

11-Dockyard Road, West Wharf Industrial Area,
P. O. Box No. 4992, Karachi-74000, Pakistan.
Tel.: +92-21-32314066 - 8 Fax: +92-21-32310421



REGIONAL OFFICE:

F-102, Regency Plaza, 120-P, Mini Market,
Gulberg-II, Lahore. Tel.: +92-42-35756728, 35757759
Fax: +92-42-35713250

E-mail: hol@haroonoils.com

www.haroonoils.com

E-mail: hollaore@haroonoils.com