



HAROON GAS ENGINE OIL

DESCRIPTION

Haroon Gas Engine Oil (0.5% SULPHATED ASH) has been formulated to provide exceptional deposit, wear, oil oxidation and oil nitration control in the high — output, highly turbo charged natural gas engine. The API — CD quality of oil demonstrate its outstanding deposit control Performance.

PERFORMANCE FEATURES

Haroon Gas Engine Oil is premium quality oil it satisfies the new generation of stationery gas engines provide exceptional deposits, wear, oil oxidation and oil nitration control in the high out put. It provides excellent piston and engine cleanliness and confirms API CD classification. It confirms US Military Performance level MIL-L-2104 C.

TYPICAL CHARACTERISTICS

HAROON GAS ENGINE OIL	
SAE Viscosity Grade	40
Gravity , @ API (ASTM D 286)	26
Flash Point, °C (ASTM D 92)	260
Pour Point, °C (ASTM D 97)	-15
Viscosity	
CSt @ 40 °C ASTM D 445	135
CSt @ 100 °C (ASTM D 445)	13.9
Viscosity Index (ASTM D 567)	99
Sulphated Ash % wt (ASTM D 874)	0.51
TBN, mg KOH/g (ASTM D 2896)	5.2

APPLICATIONS

- Recommended for highly turbo charged natural gas engines.
- Meets the requirements for stationary gas engines fueled by natural gas.
- Maximum protection against piston scuffing, scoring, and piston/cylinder liner wear.
- Improved piston cleanliness and control carbon deposits.
- Excellent foam and corrosion resistance.

NTN: 1360213 - 6

HEAD OFFICE:

11-Dockyard Road, West Wharf Industrial Area,
P. O. Box No. 4992, Karachi-74000, Pakistan.
Tel.: +92-21-32314066 - 8 Fax: +92-21-32310421



REGIONAL OFFICE:

F-102, Regency Plaza, 120-P, Mini Market,
Gulberg-II, Lahore. Tel.: +92-42-35756728, 35757759
Fax: +92-42-35713250

E-mail: hol@haroonoils.comwww.haroonoils.comE-mail: hollaore@haroonoils.com